

MAC AUDIO

Int. kód	Názov	aktivne	MOC bez DPH
FEARLESSONE	Zosilňovač Fearless One	6,000	150,000
DS01199	Kondenzátor Elko E/17; 50V; 3300nF	1,000	0,000
MP225BP	Subwoofer MP 225 BP; bandpass; 10" x 2; 2 x 100W/300-600W; 4 Ohm; 24-500Hz; citlivosť	1,000	70,000
FEARLESSTWO	Zosilňovač Fearless Two	7,000	85,000
ALIANTE10B	Subwoofer Aliente Black Limited 10; 10"; 400/1000W pri 4 Ohm; 20-250Hz; citlivosť 87dB	1,000	170,000
PROFLAT13.2	Reproduktory Pro Flat 13.2; pár; 2-pásmový koax systém; 130mm; 60/220W pri 4 Ohm; 38-	1,000	30,000
PROFLAT2.13	Reproduktory Pro Flat 2.13; pár; 2-pásmový kompo systém; 130mm; 70/250W pri 4 Ohm; 3	9,000	30,000
ZX4500	Zosilňovač ZX 4500; max. výkon 4x250W (4 Ohm); max. výkon 4x300W (2 Ohm)	12,000	80,000
D1192130	Reproduktory Mac Iron 2.13; pár	3,000	52,800
STX15	Subwoofer STX 15; 380mm; 600/1200W pri 4 Ohm; 18-500Hz; citlivosť 93dB	1,000	45,000
SUPERAUDIO69.2	Reproduktory Super Audio 69.2; pár; 2-pásmový koaxiál systém; 6x9"; 100/200W pri 4 Ohm	7,000	40,000
MPXTUBE112	Subwoofer MPX Tube 112; bassreflex; 12"; 250/800W pri 4 Ohm; 22-500Hz; citlivosť 90dB	2,000	30,000
D4328131	Reproduktor subwooferu ST212; 12" (32cm); výkon RMS 300W; max. 1000W pri 4 Ohm; 21	1,000	30,000
ALIANTE12B	Subwoofer Aliente Black Limited 12; 12"; 500/1200W pri 4 Ohm; 18-250Hz; citlivosť 88dB	3,000	120,000
MP2.13	Reproduktory MP 2.13; pár; 2-pásmový kompo systém; 130mm; 60/120W pri 4 Ohm; 39-23	2,000	19,500
MICROX1000	Zosilňovač Micro X 1000; max. výkon 800W (4 Ohm); RMS 350W (4 Ohm)	2,000	100,000
MICROX2000	Zosilňovač Micro X 2000; max. výkon 2x250W (4 Ohm); RMS 2x240W (4 Ohm)	2,000	70,000
FEARLESS2100D	Zosilňovač Fearless 2100D	9,000	80,000
ICECUBE108F	Subwoofer Ice Cube 108F; aktívny 8"; 500/150W pri 10 Ohm; 25-150 Hz	1,000	110,000
STX112RREFERENC	Subwoofer STX 112 R reference; bassreflex; 12"; 1000/2000W pri 4 Ohm; 18-500Hz; citlivosť	1,000	120,000
ICECUBE112P	Subwoofer Ice Cube 112P; bandpass 12"; 400/1200W pri 4 Ohm; 20-500 Hz; citlivosť 92dB	1,000	85,000

73,000